

## 属性

|      |   |
|------|---|
| 原料   | 钢   |
| 应用范围 | 针对摆动的软管的人员保护。   |
| 温度范围 | -30°C 至 +150°C  |
| 许可   | BGR 237<br>DIN EN ISO 4413<br>BGI 5100<br>机械指令 2006/42/EG |



## 货品

| 名称                 | 用于机器固定点直径   | 用于软管 DN | 用于软管外径-Ø  | 最大工作压力 (bar) |
|--------------------|-------------|---------|-----------|--------------|
| STOP LOCK 45 85    | 11.5-15.5mm | 02 - 04 | 4.5-8.5mm | 630          |
| STOP LOCK 1119     | 12-20mm     | 05 - 08 | 11-19mm   | 450          |
| STOP LOCK 1119 UHP | 12-20mm     | 06      | 11-19mm   | 700          |
| STOP LOCK 1728     | 18-24mm     | 10 - 12 | 17-28mm   | 450          |
| STOP LOCK 2331     | 22-30mm     | 16      | 23-31mm   | 420          |
| STOP LOCK 2635     | 28-36mm     | 19      | 26-35mm   | 420          |
| STOP LOCK 3444     | 32-42mm     | 25      | 34-44mm   | 420          |
| STOP LOCK 4352     | 38-52mm     | 31      | 43-52mm   | 210          |
| STOP LOCK 5061     | 44-52mm     | 38      | 50-61mm   | 200          |
| STOP LOCK 6074     | 56-62mm     | 51      | 60-74mm   | 185          |
| STOP LOCK 4352 HP  | 38-52mm     | 31      | 43-52mm   | 350          |
| STOP LOCK 5061 HP  | 44-52mm     | 38      | 50-61mm   | 310          |
| STOP LOCK 6074 HP  | 56-62mm     | 51      | 60-74mm   | 270          |
| STOP LOCK 4352 UHP | 38-52mm     | 31      | 43-52mm   | 500          |
| STOP LOCK 5061 UHP | 44-52mm     | 38      | 50-61mm   | 450          |
| STOP LOCK 6074 UHP | 56-62mm     | 51      | 60-74mm   | 420          |

## 附件

|                |               |
|----------------|---------------|
| STOP LOCK-KIT  | 软管压紧式固定装置工具套件 |
| STOP LOCK-TAPE | 软管压紧式固定带      |